

```

<?xml version="1.0" encoding="utf-8"?>
| <!-- edited with XMLSpy v2013v2014 rel. 2 sp2sp1 (x64) (http://www.altova.com) by - - (Agency for the
Cooperation of Energy Regulators) -->
| <xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
| xmlns:ait1="http://www.acer.europa.eu/REMIT/REMITTable1_V4V2.xsd"
| targetNamespace="http://www.acer.europa.eu/REMIT/REMITTable1_V4V2.xsd"
| elementFormDefault="qualified">
|   <xs:element name="REMITTable1">
|     <xs:complexType>
|       <xs:sequence>
|         <xs:element name="reportingEntityID" type="ait1:reportingEntityID">
|           <xs:annotation>
|             <xs:documentation>Field No. 6, 7</xs:documentation>
|           </xs:annotation>
|         </xs:element>
|         <xs:element name="contractList" type="ait1:contractListType"
minOccurs="0"/>
|         <xs:element name="OrderList" type="ait1:OrderListType"
minOccurs="0">
|           <xs:unique name="OrderRecordSeqNumber">
|             <xs:selector xpath="ait1:OrderReport"/>
|             <xs:field xpath="ait1:RecordSeqNumber"/>
|           </xs:unique>
|         </xs:element>
|         <xs:element name="TradeList" type="ait1:TradeListType"
minOccurs="0">
|           <xs:unique name="TradeRecordSeqNumber">
|             <xs:selector xpath="ait1:TradeReport"/>
|             <xs:field xpath="ait1:RecordSeqNumber"/>
|           </xs:unique>
|         </xs:element>
|       </xs:sequence>
|     </xs:complexType>
|   </xs:element>
|   <xs:complexType name="annexTable1ContractType">
|     <xs:sequence>
|       <xs:element name="contractId" type="ait1:contractIdType">
|         <xs:annotation>
|           <xs:documentation>Field No. 21</xs:documentation>
|         </xs:annotation>
|       </xs:element>
|       <xs:element name="contractName" type="ait1:contractNameType"
minOccurs="0">
|         <xs:annotation>
|           <xs:documentation>Field No. 22 </xs:documentation>
|         </xs:annotation>
|       </xs:element>
|       <xs:element name="contractType" type="ait1:contractTypeType">
|         <xs:annotation>
|           <xs:documentation>Field No. 23</xs:documentation>
|         </xs:annotation>
|       </xs:element>
|       <xs:element name="energyCommodity" type="ait1:energyCommodityType"
maxOccurs="2">
|         <xs:annotation>
|           <xs:documentation>Field No. 24</xs:documentation>

```

```

        </xs:annotation>
      </xs:element>
      <xs:element name="fixingIndex" type="ait1:fixingIndexDetails" minOccurs="0"
maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Field No. 25</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="settlementMethod" type="ait1:settlementMethodType"
default="P">
        <xs:annotation>
          <xs:documentation>Field No. 26</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="organisedMarketPlaceIdentifier"
type="ait1:organisedMarketPlaceType">
        <xs:annotation>
          <xs:documentation>Field No. 27</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="contractTradingHours"
type="ait1:contractTradingHoursType" minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Field No. 28</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="lastTradingDateTime" type="xs:dateTime" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No. 29</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="optionDetails" type="ait1:optionDetails" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Fields No. 44, 45, 46 and
47</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="deliveryPointOrZone" type="ait1:eic"
maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Field No. 48</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="deliveryStartDate" type="xs:date">
        <xs:annotation>
          <xs:documentation>Field No. 49</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="deliveryEndDate" type="xs:date">
        <xs:annotation>
          <xs:documentation>Field No. 50</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="duration" type="ait1:durationType" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No. 51</xs:documentation>

```

```

        </xs:annotation>
      </xs:element>
      <xs:element name="loadType" type="ait1:contractLoadType" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No. 52</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="deliveryProfile" type="ait1:deliveryProfileDetails"
maxOccurs="unbounded"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="annexTable1Order">
    <xs:sequence>
      <xs:element name="RecordSeqNumber" type="ait1:RecordSeqNumberType"/>
      <xs:element name="idOfMarketParticipant" type="ait1:participantType">
        <xs:annotation>
          <xs:documentation>Field No. 1, Field No. 2
        </xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="traderID" type="ait1:traderIDType">
        <xs:annotation>
          <xs:documentation>Field No 3</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="beneficiaryIdentification" type="ait1:participantType"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No. 8,Field No. 9</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="tradingCapacity" type="ait1:tradingCapacityType">
        <xs:annotation>
          <xs:documentation>Field No. 10</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="buySellIndicator" type="ait1:buySellIndicatorType">
        <xs:annotation>
          <xs:documentation>Field No. 11</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="orderId" type="ait1:orderIdType">
        <xs:annotation>
          <xs:documentation>Field No. 13</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="orderType" type="ait1:orderTypesType">
        <xs:annotation>
          <xs:documentation>Field No. 14</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="orderCondition" type="ait1:orderConditionsType"
minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Field No. 15</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>

```

```

        </xs:element>
        <xs:element name="orderStatus" type="ait1:orderStatusType" minOccurs="0"
maxOccurs="unbounded">
            <xs:annotation>
                <xs:documentation>Field No. 16</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="minimumExecuteVolume" type="ait1:quantityType"
minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 17</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="triggerDetails" type="ait1:triggerDetailsType"
minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 18</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="undisclosedVolume" type="ait1:quantityType"
minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 19</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="orderDuration" type="ait1:orderDurationType">
            <xs:annotation>
                <xs:documentation>Field No. 20</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="contractInfo" type="ait1:contractInfoType"/>
        <xs:element name="organisedMarketPlaceIdentifier"
type="ait1:organisedMarketPlaceType">
            <xs:annotation>
                <xs:documentation>Field No. 27 </xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="transactionTime" type="xs:dateTime">
            <xs:annotation>
                <xs:documentation>Field No. 30</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="originalEntryTime" type="xs:dateTime" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 30</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="linkedOrderId" type="ait1:orderIdIdentifierType"
minOccurs="0" maxOccurs="unbounded">
            <xs:annotation>
                <xs:documentation>Field No. 33</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="priceDetails" type="ait1:priceDetailsType" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 35, 36 and 37</xs:documentation>
            </xs:annotation>
        </xs:element>

```

```

        </xs:annotation>
      </xs:element>
      <xs:element name="notionalAmountDetails"
type="ait1:notionalAmountDetailsType" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No 38 and 39</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="quantity" type="ait1:quantityType" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No 40 and 42</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="totalNotionalContractQuantity"
type="ait1:notionalQuantityType" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No 41 and 42</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="priceIntervalQuantityDetails"
type="ait1:priceTimeIntervalQuantityDetails" minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Field No 49, 50 ,53, 54, 55, 56 and
57</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="actionType" type="ait1:actionTypesType">
        <xs:annotation>
          <xs:documentation>Field No. 58</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="Extra" type="ait1:extraType" minOccurs="0"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="annexTable1Trade">
    <xs:sequence>
      <xs:element name="RecordSeqNumber" type="ait1:RecordSeqNumberType"/>
      <xs:element name="idOfMarketParticipant" type="ait1:participantType">
        <xs:annotation>
          <xs:documentation>Field No. 1, Field No. 2
</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="traderID" type="ait1:traderIDType" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No 3</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="otherMarketParticipant" type="ait1:participantType"
minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No. 4, Field No. 5
</xs:documentation>
        </xs:annotation>
      </xs:element>

```

```

minOccurs="0">
    <xs:element name="beneficiaryIdentification" type="ait1:participantType"
        <xs:annotation>
            <xs:documentation>Field No. 8,Field No. 9</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="tradingCapacity" type="ait1:tradingCapacityType">
        <xs:annotation>
            <xs:documentation>Field No. 10</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="buySellIndicator" type="ait1:buySellIndicatorType">
        <xs:annotation>
            <xs:documentation>Field No. 11</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="aggressor" type="ait1:aggressorType" minOccurs="0">
        <xs:annotation>
            <xs:documentation>Field No. 12</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="clickAndTradeDetails" type="ait1:clickAndTradeDetailsType"
minOccurs="0">
        <xs:annotation>
            <xs:documentation>Optional e.g. to be used for Click Trade
when aggressor doesn't submit an order</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="contractInfo" type="ait1:contractInfoType_1"/>
    <xs:element name="organisedMarketPlaceIdentifier"
type="ait1:organisedMarketPlaceType">
        <xs:annotation>
            <xs:documentation>Field No. 27</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="transactionTime" type="xs:dateTime">
        <xs:annotation>
            <xs:documentation>Field No. 30</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="executionTime" type="xs:dateTime" minOccurs="0">
        <xs:annotation>
            <xs:documentation>Field No. 3030 if different than transaction
time</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="uniqueTransactionIdentifier" type="ait1:tradeIdType">
        <xs:annotation>
            <xs:documentation>Field No. 31</xs:documentation>
        </xs:annotation>
    </xs:element>
    <xs:element name="linkedTransactionId"
type="ait1:uniqueTransactionIdentifierType" minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
            <xs:documentation>Field No. 32</xs:documentation>
        </xs:annotation>

```

```

        </xs:element>
        <xs:element name="linkedOrderId" type="ait1:orderIdIdentifierType"
minOccurs="0" maxOccurs="unbounded">
            <xs:annotation>
                <xs:documentation>Field No. 33</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="voiceBrokered" type="xs:boolean"
default="false" ait1:booleanType" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 34</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="priceDetails" type="ait1:priceDetailsType" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 35, 36 and 37</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="notionalAmountDetails"
type="ait1:notionalAmountDetailsType" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No 38 and 39</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="quantity" type="ait1:quantityType" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 40</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="totalNotionalContractQuantity"
type="ait1:notionalQuantityType" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 41</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="terminationDate" type="xs:dateTime" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 43</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="priceIntervalQuantityDetails"
type="ait1:priceTimeIntervalQuantityDetails" minOccurs="0" maxOccurs="unbounded">
            <xs:annotation>
                <xs:documentation>Fields No 53, 54, 55, 56 and 57
</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="actionType" type="ait1:actionTypesType">
            <xs:annotation>
                <xs:documentation>Field No. 58</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="Extra" type="ait1:extraType" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="clickAndTradeDetailsType">

```

```

        <xs:sequence>
          <xs:element name="orderType" type="ait1:orderTypesType"
maxOccurs="unbounded">
            <xs:annotation>
              <xs:documentation>Field No. 14</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="orderCondition" type="ait1:orderConditionsType"
minOccurs="0" maxOccurs="unbounded">
            <xs:annotation>
              <xs:documentation>Field No. 15</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="orderStatus" type="ait1:orderStatusType" minOccurs="0"
maxOccurs="unbounded">
            <xs:annotation>
              <xs:documentation>Field No. 16</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="minimumExecuteVolume" type="ait1:quantityType"
minOccurs="0">
            <xs:annotation>
              <xs:documentation>Field No. 17</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="triggerDetails" type="ait1:triggerDetailsType"
minOccurs="0">
            <xs:annotation>
              <xs:documentation>Field No. 18</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="undisclosedVolume" type="ait1:quantityType"
minOccurs="0">
            <xs:annotation>
              <xs:documentation>Field No. 19</xs:documentation>
            </xs:annotation>
          </xs:element>
          <xs:element name="orderDuration" type="ait1:orderDurationType"
minOccurs="0">
            <xs:annotation>
              <xs:documentation>Field No. 20</xs:documentation>
            </xs:annotation>
          </xs:element>
        </xs:sequence>
      </xs:complexType>
      <xs:complexType name="contractInfoType">
        <xs:choice>
          <xs:sequence>
            <xs:element name="contractId" type="ait1:contractIdType">
              <xs:annotation>
                <xs:documentation>Field No. 21</xs:documentation>
              </xs:annotation>
            </xs:element>
            <xs:element name="legContractId" type="ait1:legContractIdType"
minOccurs="0" maxOccurs="unbounded">
              <xs:annotation>

```



```

                <xs:documentation>Field No. 21</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
    <xs:sequence>
        <xs:element name="contract" type="ait1:annexTable1ContractType">
            <xs:annotation>
                <xs:documentation>Field No. 21</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="legContract" type="ait1:legContract" minOccurs="0"
maxOccurs="unbounded">
            <xs:annotation>
                <xs:documentation>Field No. 21</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
</xs:choice>
</xs:complexType>
<xs:complexType name="contractInfoType_1">
    <xs:choice>
        <xs:element name="contractId" type="ait1:contractIdType">
            <xs:annotation>
                <xs:documentation>Field No. 21</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="contract" type="ait1:annexTable1ContractType">
            <xs:annotation>
                <xs:documentation>Field No. 21</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:choice>
</xs:complexType>
<xs:complexType name="contractListType">
    <xs:sequence>
        <xs:element name="contract" type="ait1:annexTable1ContractType"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="contractTradingHoursType">
    <xs:sequence>
        <xs:element name="startTime" type="xs:time"/>
        <xs:element name="endTime" type="xs:time"/>
        <xs:element name="date" type="xs:date" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="deliveryProfileDetails">
    <xs:sequence>
        <xs:element name="loadDeliveryStartDate" type="xs:date" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 49</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="loadDeliveryEndDate" type="xs:date" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 50</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
</xs:complexType>

```

```

        </xs:annotation>
      </xs:element>
      <xs:element name="daysOfTheWeek" type="ait1:daysOfTheWeekType"
minOccurs="0" maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Field No. 53</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:sequence maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Field No. 54</xs:documentation>
        </xs:annotation>
        <xs:element name="loadDeliveryStartTime" type="xs:time">
          <xs:annotation>
            <xs:documentation>Field No. 54</xs:documentation>
          </xs:annotation>
        </xs:element>
        <xs:element name="loadDeliveryEndTime" type="xs:time">
          <xs:annotation>
            <xs:documentation>Field No. 54</xs:documentation>
          </xs:annotation>
        </xs:element>
      </xs:sequence>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="fixingIndexDetails">
    <xs:sequence>
      <xs:element name="indexName" type="ait1:fixingIndexType">
        <xs:annotation>
          <xs:documentation>Field No. 25</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="indexValue" type="ait1:number" minOccurs="0">
        <xs:annotation>
          <xs:documentation/>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="intervalQuantityType">
    <xs:sequence>
      <xs:element name="quantity" type="ait1:number"/>
      <xs:element name="unit" type="ait1:quantityUnitType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="legContract">
    <xs:sequence>
      <xs:element name="contract" type="ait1:annexTable1ContractType"/>
      <xs:element name="buySellIndicator" type="ait1:buySellIndicatorType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="legContractIdType">
    <xs:sequence>
      <xs:element name="contractId" type="ait1:contractIdType">
        <xs:annotation>
          <xs:documentation>Field No. 21</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>

```

```

        </xs:annotation>
      </xs:element>
      <xs:element name="buySellIndicator" type="ait1:buySellIndicatorType"/>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="notionalAmountDetailsType">
    <xs:sequence>
      <xs:element name="notionalAmount" type="ait1:number">
        <xs:annotation>
          <xs:documentation>Field No. 38</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="notionalCurrency" type="ait1:currencyCodeType">
        <xs:annotation>
          <xs:documentation>Field No. 39</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="notionalQuantityType">
    <xs:sequence>
      <xs:element name="value" type="ait1:number"/>
      <xs:element name="unit" type="ait1:notionalQuantityUnitType">
        <xs:annotation>
          <xs:documentation>Field No 42 for 41</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="optionDetails">
    <xs:sequence>
      <xs:element name="optionStyle" type="ait1:optionStyleType">
        <xs:annotation>
          <xs:documentation>Field No. 44</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="optionType" type="ait1:optionTypeType">
        <xs:annotation>
          <xs:documentation>Field No. 45</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="optionExerciseDate" type="xs:date" timedate minOccurs="0"
maxOccurs="unbounded">
        <xs:annotation>
          <xs:documentation>Field No. 46</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="optionStrikePrice" type="ait1:priceType" minOccurs="0">
        <xs:annotation>
          <xs:documentation>Field No. 47</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
  </xs:complexType>
  <xs:complexType name="orderDurationType">
    <xs:sequence>

```

```

        <xs:element name="duration" type="ait1:orderDurationsType"/>
        <xs:element name="expirationDateTime" type="xs:dateTime" minOccurs="0"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="orderIdType">
    <xs:sequence>
        <xs:element name="uniqueOrderIdentifier" type="ait1:orderIdentifierType">
            <xs:annotation>
                <xs:documentation>Field No. 13</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="previousOrderIdentifier" type="ait1:orderIdentifierType"
minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 13 - Previous Order
ID</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="OrderListType">
    <xs:sequence>
        <xs:element name="OrderReport" type="ait1:annexTable1Order"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="organisedMarketPlaceType">
    <xs:choice>
        <xs:element name="lei" type="ait1:lei"/>
        <xs:element name="mic" type="ait1:mic"/>
        <xs:element name="ace" type="ait1:ace"/>
        <xs:element name="bil" type="ait1:bil"/>
    </xs:choice>
</xs:complexType>
<xs:complexType name="participantType">
    <xs:choice>
        <xs:element name="ace" type="ait1:ace"/>
        <xs:element name="lei" type="ait1:lei"/>
        <xs:element name="bic" type="ait1:bic"/>
        <xs:element name="eic" type="ait1:eic"/>
        <xs:element name="gln" type="ait1:gln"/>
    </xs:choice>
</xs:complexType>
<xs:complexType name="priceDetailsType">
    <xs:sequence>
        <xs:element name="price" type="ait1:number">
            <xs:annotation>
                <xs:documentation>Field No. 35</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="priceCurrency" type="ait1:currencyCodeType">
            <xs:annotation>
                <xs:documentation>Field No. 37</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>

```

```

</xs:complexType>
<xs:complexType name="priceTimeIntervalQuantityDetails">
  <xs:sequence>
    <xs:element name="intervalStartDate" type="xs:date" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Field No. 49</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="intervalEndDate" type="xs:date" minOccurs="0">
      <xs:annotation>
        <xs:documentation>Field No. 50</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:element name="daysOfTheWeek" type="ait1:daysOfTheWeekType"
minOccurs="0">
      <xs:annotation>
        <xs:documentation>Field 53</xs:documentation>
      </xs:annotation>
    </xs:element>
    <xs:sequence maxOccurs="unbounded">
      <xs:annotation>
        <xs:documentation>Field No. 54</xs:documentation>
      </xs:annotation>
      <xs:element name="intervalStartTime" type="xs:time">
        <xs:annotation>
          <xs:documentation>Field No. 54</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="intervalEndTime" type="xs:time">
        <xs:annotation>
          <xs:documentation>Field No. 54</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
    <xs:sequence minOccurs="0">
      <xs:element name="quantity" type="ait1:number">
        <xs:annotation>
          <xs:documentation>Field No. 55</xs:documentation>
        </xs:annotation>
      </xs:element>
      <xs:element name="unit" type="ait1:quantityUnitType">
        <xs:annotation>
          <xs:documentation>Field No. 56</xs:documentation>
        </xs:annotation>
      </xs:element>
    </xs:sequence>
    <xs:element name="priceTimeIntervalQuantity" type="ait1:priceType"
minOccurs="0">
      <xs:annotation>
        <xs:documentation>Field 57</xs:documentation>
      </xs:annotation>
    </xs:element>
  </xs:sequence>
</xs:complexType>
<xs:complexType name="priceType">
  <xs:sequence>

```

```

        <xs:element name="value" type="ait1:number"/>
        <xs:element name="currency" type="ait1:currencyCodeType"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="quantityType">
    <xs:sequence>
        <xs:element name="value" type="ait1:number"/>
        <xs:element name="unit" type="ait1:quantityUnitType">
            <xs:annotation>
                <xs:documentation>Field No 42 for 40</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="reportingEntityID">
    <xs:choice>
        <xs:element name="ace" type="ait1:ace"/>
        <xs:element name="lei" type="ait1:lei"/>
        <xs:element name="bic" type="ait1:bic"/>
        <xs:element name="eic" type="ait1:eic"/>
        <xs:element name="gln" type="ait1:gln"/>
    </xs:choice>
</xs:complexType>
<xs:complexType name="tradeIdType">
    <xs:sequence>
        <xs:element name="uniqueTransactionIdentifier"
type="ait1:uniqueTransactionIdentifierType">
            <xs:annotation>
                <xs:documentation>Field No. 31</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="previousUniqueTransactionIdentifieradditionalUtilInfo"
type="ait1:uniqueTransactionIdentifierType" minOccurs="0">
            <xs:annotation>
                <xs:documentation>Field No. 31</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="TradeListType">
    <xs:sequence>
        <xs:element name="TradeReport" type="ait1:annexTable1Trade"
maxOccurs="unbounded"/>
    </xs:sequence>
</xs:complexType>
<xs:complexType name="traderIDType">
    <xs:choice>
        <xs:element name="traderIdForOrganisedMarket" type="ait1:traderCode">
            <xs:annotation>
                <xs:documentation>Field No. 3a</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="traderIdForMarketParticipant" type="ait1:traderCode">
            <xs:annotation>
                <xs:documentation>Field No. 3b</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:choice>
</xs:complexType>

```

```

        </xs:element>
    </xs:choice>
</xs:complexType>
<xs:complexType name="triggerDetailsType">
    <xs:sequence>
        <xs:element name="priceLimit" type="ait1:priceType">
            <xs:annotation>
                <xs:documentation>Field No. 18</xs:documentation>
            </xs:annotation>
        </xs:element>
        <xs:element name="triggerContractId" type="ait1:contractIdType"
minOccurs="0">
            <xs:annotation>
                <xs:documentation>Contract ID of different contract (triggering
contract)</xs:documentation>
            </xs:annotation>
        </xs:element>
    </xs:sequence>
</xs:complexType>
<xs:simpleType name="ace">
    <xs:restriction base="xs:string">
        <xs:maxLength value="12"/>
        <xs:minLength value="12"/>
        <xs:pattern value="[A-Za-z0-9_]+\.[A-Z][A-Z]"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="actionTypesType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="N"/>
        <xs:enumeration value="M"/>
        <xs:enumeration value="E"/>
        <xs:enumeration value="C"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="aggressorType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="A"/>
        <xs:enumeration value="I"/>
        <xs:enumeration value="S"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="bic">
    <xs:restriction base="xs:string">
        <xs:maxLength value="11"/>
        <xs:minLength value="11"/>
        <xs:pattern value="[A-Za-z0-9_]+"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="bil">
    <xs:restriction base="xs:string">
        <xs:enumeration value="XBIL"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="booleanType">
    <xs:restriction base="xs:string">
        <xs:pattern value="XBIL"/>="(true)|(Y)|(false)|(N)"/>

```

```

</xs:restriction>
</xs:simpleType>
<xs:simpleType name="buySellIndicatorType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="B"/>
    <xs:enumeration value="S"/>
    <xs:enumeration value="C"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="contractIdType">
  <xs:restriction base="xs:string">
    <xs:maxLength value="50"/>
    <xs:pattern value="[A-Za-z0-9_-]+"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="contractLoadType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="BL"/>
    <xs:enumeration value="PL"/>
    <xs:enumeration value="OP"/>
    <xs:enumeration value="BH"/>
    <xs:enumeration value="SH"/>
    <xs:enumeration value="GD"/>
    <xs:enumeration value="OT"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="contractNameType">
  <xs:restriction base="xs:string">
    <xs:maxLength value="400200"/>
    <xs:pattern value="[A-Za-z0-9_]+"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="contractTypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="AU"/>
    <xs:enumeration value="CO"/>
    <xs:enumeration value="FW"/>
    <xs:enumeration value="FU"/>
    <xs:enumeration value="OP"/>
    <xs:enumeration value="OP_FW"/>
    <xs:enumeration value="OP_FU"/>
    <xs:enumeration value="OP_SW"/>
    <xs:enumeration value="SP"/>
    <xs:enumeration value="SW"/>
    <xs:enumeration value="OT"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="currencyCodeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="BGN"/>
    <xs:enumeration value="CHF"/>
    <xs:enumeration value="CZK"/>
    <xs:enumeration value="DKK"/>
    <xs:enumeration value="EUR"/>
    <xs:enumeration value="EUX"/>
    <xs:enumeration value="GBX"/>
  </xs:restriction>
</xs:simpleType>

```



```

        <xs:enumeration value="GBP"/>
        <xs:enumeration value="HRK"/>
        <xs:enumeration value="HUF"/>
        <xs:enumeration value="ISK"/>
        <xs:enumeration value="NOK"/>
        <xs:enumeration value="PCT"/>
        <xs:enumeration value="PLN"/>
        <xs:enumeration value="RON"/>
        <xs:enumeration value="SEK"/>
        <xs:enumeration value="USD"/>
        <xs:enumeration value="OTH"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="daysOfTheWeekType">
    <xs:restriction base="xs:string">
        <xs:pattern
value="((SU|MO|TU|WE|TH|FR|SA)to(SU|MO|TU|WE|TH|FR|SA))((SU|MO|TU|WE|TH|FR|SA|XB|IB|WD|WN)"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="durationType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="N"/>
        <xs:enumeration value="H"/>
        <xs:enumeration value="D"/>
        <xs:enumeration value="W"/>
        <xs:enumeration value="M"/>
        <xs:enumeration value="Q"/>
        <xs:enumeration value="S"/>
        <xs:enumeration value="Y"/>
        <xs:enumeration value="O"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="eic">
    <xs:restriction base="xs:string">
        <xs:maxLength value="16"/>
        <xs:minLength value="16"/>
        <xs:pattern value="[0-9][0-9][XYZTWV].+"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="energyCommodityType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="EL"/>
        <xs:enumeration value="NG"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="extraType">
    <xs:restriction base="xs:string">
        <xs:maxLength value="1000"/>
        <xs:pattern value="[A-Za-z0-9_
}+>="((\w+==((\d+\.\d+)|(\d+)|(\w+));)+(\w+==((\d+\.\d+)|(\d+)|(\w+))))"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="fixingIndexType">
    <xs:restriction base="xs:string">
        <xs:maxLength value="150"/>

```

```

        <xs:pattern value="[A-Za-z0-9_ ]+>[-]+"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="gln">
    <xs:restriction base="xs:string">
        <xs:maxLength value="13"/>
        <xs:minLength value="13"/>
        <xs:pattern value="[A-Za-z0-9 ]+>[-]+"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="lei">
    <xs:restriction base="xs:string">
        <xs:maxLength value="20"/>
        <xs:minLength value="20"/>
        <xs:pattern value="[A-Za-z0-9_ ]+>[-]+"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="mic">
    <xs:restriction base="xs:string">
        <xs:maxLength value="4"/>
        <xs:minLength value="4"/>
        <xs:pattern value="[A-Za-z0-9_ ]+>[-]+"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="notionalQuantityUnitType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="KWh"/>
        <xs:enumeration value="MWh"/>
        <xs:enumeration value="GWh"/>
        <xs:enumeration value="Therm"/>
        <xs:enumeration value="KTherm"/>
        <xs:enumeration value="MTherm"/>
        <xs:enumeration value="cm"/>
        <xs:enumeration value="mcm"/>
        <xs:enumeration value="Btu"/>
        <xs:enumeration value="MMBtu"/>
        <xs:enumeration value="MJ"/>
        <xs:enumeration value="100MJ"/>
        <xs:enumeration value="MMJ"/>
        <xs:enumeration value="GJ"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="number">
    <xs:restriction base="xs:decimal">
        <xs:totalDigits value="20"/>
        <xs:fractionDigits value="5"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="optionStyleType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="A"/>
        <xs:enumeration value="B"/>
        <xs:enumeration value="E"/>
        <xs:enumeration value="S"/>
        <xs:enumeration value="O"/>
    </xs:restriction>

```

```
</xs:simpleType>
<xs:simpleType name="optionTypeType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="C"/>
    <xs:enumeration value="P"/>
    <xs:enumeration value="O"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="orderConditionsType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="AON"/>
    <xs:enumeration value="FAF"/>
    <xs:enumeration value="FAK"/>
    <xs:enumeration value="FOK"/>
    <xs:enumeration value="HVO"/>
    <xs:enumeration value="MEV"/>
    <xs:enumeration value="OCO"/>
    <xs:enumeration value="PRE"/>
    <xs:enumeration value="PRI"/>
    <xs:enumeration value="PTR"/>
    <xs:enumeration value="SLO"/>
    <xs:enumeration value="OTH"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="orderDurationsType">
  <xs:restriction base="xs:string">
    <xs:enumeration value="DAY"/>
    <xs:enumeration value="GTC"/>
    <xs:enumeration value="GTD"/>
    <xs:enumeration value="GTT"/>
    <xs:enumeration value="SES"/>
    <xs:enumeration value="OTH"/>
  </xs:restriction>
</xs:simpleType>
<xs:simpleType name="orderIdIdentifierType">
  <xs:restriction base="xs:string">
    <xs:maxLength value="100"/>
    <xs:pattern value="[A-Za-z0-9_ ]+|/|-|+|_|!|@|&|#|~|`|'|\"/>
```

```

        <xs:enumeration value="CON"/>
        <xs:enumeration value="COM"/>
        <xs:enumeration value="EXC"/>
        <xs:enumeration value="FHR"/>
        <xs:enumeration value="IOI"/>
        <xs:enumeration value="LIM"/>
        <xs:enumeration value="LIN"/>
        <xs:enumeration value="LIS"/>
        <xs:enumeration value="MAR"/>
        <xs:enumeration value="MTL"/>
        <xs:enumeration value="SMA"/>
        <xs:enumeration value="SPR"/>
        <xs:enumeration value="STP"/>
        <xs:enumeration value="VBL"/>
        <xs:enumeration value="OTH"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="quantityUnitType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="KW"/>
        <xs:enumeration value="KWh/h"/>
        <xs:enumeration value="KWh/d"/>
        <xs:enumeration value="MW"/>
        <xs:enumeration value="MWh/h"/>
        <xs:enumeration value="MWh/d"/>
        <xs:enumeration value="GW"/>
        <xs:enumeration value="GWh/h"/>
        <xs:enumeration value="GWh/d"/>
        <xs:enumeration value="Therm/d"/>
        <xs:enumeration value="KTherm/d"/>
        <xs:enumeration value="MTherm/d"/>
        <xs:enumeration value="cm/d"/>
        <xs:enumeration value="mcm/d"/>
        <xs:enumeration value="Btu/d"/>
        <xs:enumeration value="MMBtu/d"/>
        <xs:enumeration value="MJ/d"/>
        <xs:enumeration value="100MJ/d"/>
        <xs:enumeration value="MMJ/d"/>
        <xs:enumeration value="GJ/d"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="RecordSeqNumberType">
    <xs:restriction base="xs:integer">
        <xs:minInclusive value="1"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="restrictedString">
    <xs:restriction base="xs:string">
        <xs:maxLength value="100"/>
        <xs:pattern value="[A-Za-z0-9_ ]+"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="settlementMethodType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="P"/>
        <xs:enumeration value="C"/>
    </xs:restriction>
</xs:simpleType>

```

```

        <xs:enumeration value="O"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="traderCode">
    <xs:restriction base="xs:string">
        <xs:maxLength value="100"/>
        <xs:pattern value="[A-Za-z0-9_]+"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="tradingCapacityType">
    <xs:restriction base="xs:string">
        <xs:enumeration value="P"/>
        <xs:enumeration value="A"/>
    </xs:restriction>
</xs:simpleType>
<xs:simpleType name="uniqueTransactionIdentifierType">
    <xs:restriction base="xs:string">
        <xs:maxLength value="100"/>
        <xs:pattern value="[A-Za-z0-9_]+"/>
    </xs:restriction>
</xs:simpleType>
</xs:schema>

```